Note on English translation

This is a translation of the technical data sheet valid in Iran.

All stated details and properties are in compliance with the regulations of the Iran standards and building regulations. They are only applicable for the specified products, system components, application rules, and construction details in connection with the specifications of the respective certificates and approvals.

K plus pars denies any liability for applications outside of Iran as this requires changes acc. to the respective national standards and building regulations.





Drywall Systems

K+ Nonius Hanger

Technical Data Sheet

05/2022

K+ Nonius Hanger

Hanger Elements

Product description

Hanger used for fixing the suspended ceiling system to the structural soffit.

Storage

- Direct contact with water should be avoided.
- Packages should be stored in flat, dry and clean areas.

Standards acc. to

ISIRI 21083 and EN 13964

Properties

■ Clean and easy instalaltion

Application

Application should be done acc. to the Kplus Technical Brochures of the respective drywall system.

Field of application

Suspended Ceiling Systems

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems; Kplus Techinal Website Document Center

K+ Nonius Hanger

Hanger Elements



Technical Data

Product		Description	Length (cm)	Thickness (mm)	Weight (kg/pcs.)	Packaging unit (pcs./pallet)	«Material Number»
K+ Nonius Hanger Top		Top part of the Nonius suspension system, Attaches to nonius stirrup/Grip via Nonius Pin and is fited on to the ceiling slab (The end is only punched 20 cm)	20	1	0.042	200	943500000000020
			40		0.078		943500000000040
			60		0.114		943500000000060
			80		0.152		943500000000080
			100		0.188		943500000000100
K+ Nonius Connectors	V Tarananananan (h.)	Hanger connector to the extension piece	10	1	0.017	500	943560271510000
K+ Nonius extension piece		Used to increase the length of the hanger (Full Punch)	300	1	0.491	20	943500000003000
K+ Nonius Stirrup		Bottom part of the Nonius Suspension system which attaches to CD60/27 channel		0.6	0.04	200	943560270000000
		Bottom part of the Nonius Suspension system which attaches to F47 channel			0.032	200	943500470000000
K+ Nonius Grip		Bottom part of the Nonius Suspension system which attaches to CD60/27 channel	-	1	0.023	200	943560271000000
K+ Nonius Hanger pin		Middle part of the Nonius suspension system. Attaches Nonius Hanger Top and Nonius stirrup	-	1	0.005	300	943500028100000

Kplus Direct: Technical Support Dept.

Phone: (+98 21) 88207929Fax: (+98 21) 88203126technical@Kplus.ir

All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. The stated information represents current state-of-the-art K+ technology. The entire state of approved engineering rules, appropriate standards, guidelines, and rules of craftsmanship are not included herewith. These and all application instructions have to be adhered to separately by the installer.

All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Kplus Pars.

Head Office:

No. 19, East Qobadian Alley, Nelson Mandela (Africa) Blvd., 19176-34611, Tehran, Iran

www.Kplus.ir